

益詮切削刀具

ECHAINTOOL Cutting Tools
ECHAINTOOL Cutting Tools
ECHAINTOOL Cutting Tools



ECHAIN®



台灣精品 2008
TAIWAN EXCELLENCE



設計優良產品
GOOD DESIGN PRODUCT



第22屆小巨人獎
The 22nd Hsing Shu Award



第14屆中小企業
創新研究獎
The 14th Hsing Shu
Innovation Award



住友重工 中國一級代理
Sumitomo Agent in China

微小徑內徑車刀系列

TINY CARBIDE BORING BAR SERIES



Our web



益詮精密股份有限公司 ECHAINTOOL PRECISION CO., LTD.

TEL: +886-4-22710856 FAX: +886-4-22710857

Skype: echaintool

E-mail: sales@echaintool.com

https://www.echaintool.com

41154 台灣台中市太平區大里工業區工業18路3-1號

No.3-1, Gongye 18th Rd., Taiping Dist.,

Taichung City, 41154, Taiwan (Da-Li Industrial Park)

中国总部 Branch In China 企业QQ: 400-606-5118

National Free Call Number (In China): 400-606-5118

TEL: +86-0512-57005208 FAX: +86-0512-57005206

业务投诉专线: 18020216088

广东 / 天津 / 重庆 / 武汉 均有办事处

Branch offices are located at Guangdong, Tainjin, Chongqing and Wuhan.

微小徑內徑車刀

Tiny Carbide Boring Bar Series Index

適用於專業醫療設備、電子、化學及工業等
精密細小零件之製造加工

Apply on manufacturing and processing of precision small parts such as professional medical equipment, electronics, chemicals and industry.



- ☒ 微小徑內徑鎢鋼車刀採用全鎢鋼刀體，有效抑制加工震動
 Tiny carbide boring bar adopts a full carbide cutter body to effectively suppress the processing vibration.
- ☒ 採用超細粒子硬質合金AlTiN塗層，增加刀具耐磨耗性
 Ultra-fine particle cemented carbide AlTiN coating for increased tool wearability.
- ☒ 微小徑設計有利於狹小孔徑空間工件之切槽、仿形及倒角等加工需求
 The micro-diameter design is beneficial to the processing requirements of cutting, copying and chamfering of workpieces in narrow apertures.
- ☒ 提供精確的加工精準度和良好表面光潔度
 Provides precise machining accuracy and good surface finish.

搭配 **SHB專用套筒**
 With SHB Series Dedicated Sleeve

達到精確快速定位
 for precise and fast positioning




微小徑內徑車刀索引表 Tiny Carbide Boring Bar Series Index

產品 Product	柄徑 (D) Shank Dia.(mm)	加工徑 Min Bore Dia	塗層 Coating	頁碼 Page
GP_R 	Ø3 Ø6 Ø4 Ø8 Ø5 Ø10	1~10.1	MG	4
GQ_R 	Ø4 Ø8 Ø5 Ø6	4.1~8.1	MG	5
GT_R 	Ø3 Ø6 Ø4 Ø8 Ø5 Ø10	1~10.1	MG	6
GU_R 	Ø3 Ø6 Ø4 Ø8 Ø5	3.1~8.1	MG	7
GX_R 	Ø4 Ø5 Ø6	3.1~6.1	MG	8
GW_R 	Ø6	1	MG	9
GV_R 	Ø6 Ø8	12~20	MG	10
GG_R 	Ø3 Ø6 Ø4 Ø8 Ø5	3.1~8.1	MG	11
GK_R 	Ø4 Ø5 Ø6	4.1~6.1	MG	12
GF_L 	Ø4 Ø8 Ø5 Ø6	5~10	MG	13
GF_R 	Ø4 Ø8 Ø5 Ø6	5~10	MG	14
GD_R 	Ø4 Ø5 Ø6	4.1~6.1	MG	15
GI_R 	Ø3 Ø6 Ø4 Ø8 Ø5	2.1~8	MG	16
GZ_R 	Ø4 Ø5 Ø6	5~8	MG	17



GP_R 微小徑內徑開槽鎢鋼車刀

Tiny Grooving Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GP1RL104R005	1	0.05	0.5	0.2	3	39	4
GP1.5RL106R01	1.5	0.1	0.7	0.3	3	39	6
GP2RL110R005	2.1	0.05	0.8	0.5	3	39	10
GP2RL110R01	2.1	0.1	0.8	0.5	3	39	10
GP2RL105R015	2.1	0.15	0.8	0.5	3	39	5
GP2RL110R015	2.1	0.15	0.8	0.5	3	39	10
GP3RL110R005	3.1	0.05	1.3	0.7	3	39	10
GP3RL115R005	3.1	0.05	1.3	0.7	3	39	15
GP3RL115R01	3.1	0.1	1.3	0.7	3	39	15
GP3RL122R01	3.1	0.1	1.3	0.7	3	50	22
GP3RL110R02	3.1	0.2	1.3	0.7	3	39	10
GP3RL115R02	3.1	0.2	1.3	0.7	3	39	15
GP3RL122R02	3.1	0.2	1.3	0.7	3	50	22
GP4RL115R01	4.1	0.1	1.7	0.8	4	50	15
GP4RL122R01	4.1	0.1	1.7	0.8	4	50	22
GP4RL110R02	4.1	0.2	1.7	0.8	4	50	10
GP4RL115R02	4.1	0.2	1.7	0.8	4	50	15
GP4RL122R02	4.1	0.2	1.7	0.8	4	50	22
GP5RL122R01	5.1	0.1	2.1	1.2	5	50	22
GP5RL130R01	5.1	0.1	2.1	1.2	5	75	30
GP5RL115R02	5.1	0.2	2.1	1.2	5	50	15
GP5RL122R02	5.1	0.2	2.1	1.2	5	50	22
GP5RL130R02	5.1	0.2	2.1	1.2	5	75	30
GP6RL115R02	6.1	0.2	2.8	1.4	6	50	15
GP6RL122R02	6.1	0.2	2.8	1.4	6	50	22
GP6RL130R02	6.1	0.2	2.8	1.4	6	75	30
GP8RL115R02	8.1	0.2	3.8	1.6	8	60	15
GP8RL122R02	8.1	0.2	3.8	1.6	8	60	22
GP8RL135R02	8.1	0.2	3.8	1.6	8	75	35
GP10RL135R02	10.1	0.2	4.8	2	10	75	35



GQ_R 微小徑內徑仿型&搪孔鎢鋼車刀

Tiny Profiling & Boring Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GQ4RL110R02	4.1	0.2	1.8	0.8	4	50	10
GQ4RL115R02	4.1	0.2	1.8	0.8	4	50	15
GQ4RL122R02	4.1	0.2	1.8	0.8	4	50	22
GQ5RL115R02	5.1	0.2	2.3	1	5	50	15
GQ5RL122R02	5.1	0.2	2.3	1	5	50	22
GQ6RL115R02	6.1	0.2	2.8	1.4	6	50	15
GQ6RL122R02	6.1	0.2	2.8	1.4	6	50	22
GQ6RL130R02	6.1	0.2	2.8	1.4	6	60	30
GQ8RL122R02	8.1	0.2	3.8	1.6	8	60	22
GQ8RL127R02	8.1	0.2	3.8	2	8	60	27



GT_R 微小徑內徑車削鎢鋼車刀




Tiny Turning Carbide Boring Bar



產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	刀尖距離 F Tip Distance	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GT1RL104R005	1	0.05	0.5	3	39	4
GT1.5RL106R01	1.5	0.1	0.7	3	39	6
GT2RL110R005	2.1	0.05	0.8	3	39	10
GT2RL105R015	2.1	0.15	0.8	3	39	5
GT2RL110R015	2.1	0.15	0.8	3	39	10
GT3RL110R005	3.1	0.05	1.3	3	39	10
GT3RL115R005	3.1	0.05	1.3	3	39	15
GT3RL115R01	3.1	0.1	1.3	3	39	15
GT3RL110R02	3.1	0.2	1.3	3	39	10
GT3RL115R02	3.1	0.05	1.3	3	39	15
GT4RL115R005	4.1	0.05	1.7	4	50	15
GT4RL110R01	4.1	0.1	1.7	4	50	10
GT4RL115R01	4.1	0.1	1.7	4	50	15
GT4RL122R01	4.1	0.1	1.7	4	50	22
GT4RL110R02	4.1	0.2	1.7	4	50	10
GT4RL115R02	4.1	0.2	1.7	4	50	15
GT4RL122R02	4.1	0.2	1.7	4	50	22
GT5RL115R005	5.1	0.05	2.1	5	50	15
GT5RL115R01	5.1	0.1	2.1	5	50	15
GT5RL122R01	5.1	0.1	2.1	5	50	22
GT5RL130R01	5.1	0.1	2.1	5	75	30
GT5RL115R02	5.1	0.2	2.1	5	50	15
GT5RL122R02	5.1	0.2	2.1	5	50	22
GT5RL130R02	5.1	0.2	2.1	5	75	30
GT6RL115R005	6.1	0.05	2.8	6	50	15
GT6RL115R01	6.1	0.1	2.8	6	50	15
GT6RL115R02	6.1	0.2	2.8	6	50	15
GT6RL122R02	6.1	0.2	2.8	6	50	22
GT6RL130R02	6.1	0.2	2.8	6	60	30
GT6RL135R02	6.1	0.2	2.8	6	75	35
GT8RL115R02	8.1	0.2	3.8	8	60	15
GT8RL122R02	8.1	0.2	3.8	8	60	22
GT8RL135R02	8.1	0.2	3.8	8	75	35
GT10RL135R02	10.1	0.2	4.8	10	75	35

GU_R 微小徑內徑90° 仿型鎢鋼車刀

Tiny 90° Profiling Carbide Boring Bar




產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GU3RL110R005	3.1	0.05	1.3	0.4	3	39	10
GU3RL115R005	3.1	0.05	1.3	0.4	3	39	15
GU4RL110R01	4.1	0.1	1.7	0.5	4	50	10
GU4RL115R01	4.1	0.1	1.7	0.5	4	50	15
GU5RL115R015	5.1	0.15	2.1	0.7	5	50	15
GU5RL122R015	5.1	0.15	2.1	0.7	5	50	22
GU6RL115R015	6.1	0.15	2.8	0.9	6	50	15
GU6RL122R015	6.1	0.15	2.8	0.9	6	50	22
GU8RL122R02	8.1	0.2	3.8	1	8	60	22



GX_R 微小徑內徑後掃車削鎢鋼車刀

Tiny Bank Turning Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GX4RL110R01	3.1	0.1	1.3	0.5	4	50	10
GX4RL110R015	4.1	0.15	1.6	0.8	4	50	10
GX4RL115R015	4.1	0.15	1.6	0.8	4	50	15
GX5RL115R02	5.1	0.2	2.2	1	5	50	15
GX5RL122R02	5.1	0.2	2.2	1	5	50	22
GX6RL115R02	6.1	0.2	2.8	1.8	6	50	15
GX6RL122R02	6.1	0.2	2.8	1.8	6	50	22



GW_R 極小徑內徑倒角仿型鎢鋼車刀

Tiny Chamfering & Profiling Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	刀尖距離 F Tip Distance	夾角角度 α Included Angle	夾角角度 β Included Angle	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GW6RL115R02A90	1	0.2	2.3	45°	45°	6	50	15
GW6RL115R02A60	1	0.2	2.3	60°	30°	6	50	15



GV_R 極小徑內徑深面切斷鎢鋼車刀



Tiny Deep Face Grooving Carbide Boring Bar



產品型號 Model No	加工徑 Min Bore Dia	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GV6RL115B20	12	2	1.1	6	60	15
GV6RL122B20	12	2	1.1	6	60	22
GV6RL122B25	12	2.5	1.4	6	60	22
GV8RL127B30	15	3	1.6	8	60	27
GV8RL143B30	15	3	1.6	8	75	43
GV8RL143B40	20	4	2.1	8	75	43

GG_R 極小徑內徑開槽鎢鋼車刀

Tiny Grooving Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GG3RL110B07	3.1	0.1	0.7	1.3	0.6	3	39	10
GG4RL110B10	4.1	0.1	1	1.7	1	4	50	10
GG4RL110B15	4.1	0.1	1.5	1.7	1	4	50	10
GG5RL115B10	5.1	0.1	1	2.3	1.2	5	50	15
GG5RL115B15	5.1	0.1	1.5	2.3	1.2	5	50	15
GG5RL115B20	5.1	0.1	2	2.3	1.2	5	50	15
GG6RL115B10	6.1	0.1	1	2.8	1.4	6	50	15
GG6RL115B15	6.1	0.1	1.5	2.8	1.4	6	50	15
GG6RL115B20	6.1	0.1	2	2.8	1.4	6	50	15
GG8RL122B10	8.1	0.1	1	3.8	1.7	8	60	22
GG8RL122B15	8.1	0.1	1.5	3.8	1.7	8	60	22
GG8RL122B20	8.1	0.1	2	3.8	2.6	8	60	22



GK_R 極小徑內徑圓鼻開槽鎢鋼車刀

Tiny Full Radius Grooving Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GK4RL110R05	4.1	0.5	1	1.7	1	4	50	10
GK4RL110R075	4.1	0.75	1.5	1.7	1	4	50	10
GK5RL115R05	5.1	0.5	1	2.3	1.2	5	50	15
GK5RL115R075	5.1	0.75	1.5	2.3	1.2	5	50	15
GK5RL115R10	5.1	1	2	2.3	1.2	5	50	15
GK6RL115R05	6.1	0.5	1	2.8	1.6	6	50	15
GK6RL115R075	6.1	0.75	1.5	2.8	1.6	6	50	15
GK6RL115R10	6.1	1	2	2.8	1.6	6	50	15



GF_L 極小徑內徑平面銑削鎢鋼車刀

Tiny Facing Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GF4LL115B075	5	0.75	1.75	1.2	4	50	15
GF4LL115B10	5	1	1.75	1.5	4	50	15
GF4LL115B15	5	1.5	1.75	2.8	4	50	15
GF5LL122B075	6	0.75	2.25	1.2	5	50	22
GF5LL122B10	6	1	2.25	1.5	5	50	22
GF5LL122B15	6	1.5	2.25	2.5	5	50	22
GF5LL122B20	6	2	2.25	3.8	5	50	22
GF6LL122B10	8	1	2.75	1.5	6	50	22
GF6LL122B15	8	1.5	2.75	2.5	6	50	22
GF6LL122B20	8	2	2.75	3	6	50	22
GF6LL122B25	8	2.5	2.75	4.8	6	50	22
GF6LL130B30	8	3	2.75	6	6	60	30
GF8LL122B25	10	2.5	3.75	3.5	8	60	22



GF_R 極小徑內徑平面銑削鎢鋼車刀

Tiny Thread Relief Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GF4RL115B075	5	0.75	1.95	1.2	4	50	15
GF4RL115B10	5	1	1.95	1.5	4	50	15
GF4RL115B15	5	1.5	1.95	2.8	4	50	15
GF5RL122B075	6	0.75	2.45	1.2	5	50	22
GF5RL122B10	6	1	2.45	1.5	5	50	22
GF5RL122B15	6	1.5	2.45	2.5	5	50	22
GF5RL122B20	6	2	2.45	3.8	5	50	22
GF6RL122B10	8	1	2.95	1.5	6	50	22
GF6RL122B15	8	1.5	2.95	2.5	6	50	22
GF6RL122B20	8	2	2.95	3	6	50	22
GF6RL122B25	8	2.5	2.95	4.8	6	50	22
GF6RL130B30	8	3	2.95	6	6	60	30
GF8RL122B25	10	2.5	3.95	3.5	8	60	22



GD_R 微小徑內徑螺紋倒角鎢鋼車刀

Tiny Thread Relief Carbide Boring Bar





產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GD4RL118R05	4.1	0.5	1.5	1.8	0.8	4	50	18
GD5RL124R05	5.1	0.5	1.5	2.3	1.2	5	50	24
GD6RL127R05	6.1	0.5	1.5	2.8	1.4	6	60	27



GIR 微小徑內徑螺紋鎢鋼車刀


Tiny Threading Carbide Boring Bar



產品型號 Model No	螺距 Screw Pitch/mm	螺距 Screw Pitch/TPI	加工徑 Min Bore Dia	刀尖距離 F Tip Distance	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GIR2RL108A60	0.45-0.7	56-32	2.1	1	3	39	8
GIR3RL115A60	0.7-1	32-24	3.2	1.4	3	39	15
GIR4RL115A60	0.8-1	32-24	4.1	1.8	4	50	15
GIR5RL115A60	1-1.25	24-20	5.1	2.3	5	50	15
GIR5RL122A60	1-1.25	24-20	5.1	2.3	5	50	22
GIR6RL115A60	1-1.5	24-16	6	2.6	6	50	15
GIR6RL122A60	1-1.5	24-16	6	2.6	6	50	22
GIR8RL122A60	1-2	24-13	8	3.6	8	60	22

GZ_R 微小徑內徑端面圓槽鎢鋼車刀

Tiny Full Radius Facing Carbide Boring Bar



產品型號 Model No	加工徑 Min Bore Dia	半徑 R Radius (1/2d)	加工寬度 W Insert Processing Width	刀尖距離 F Tip Distance	加工距離 H Process Depth	柄徑 D Shank Dia	全長 L O.A.L	刃長 L1 Flut Length
GZ4RL115R05	5	0.5	1	1.95	1.2	4	50	15
GZ4RL115R075	5	0.75	1.5	1.95	1.5	4	50	15
GZ5RL122R05	6	0.5	1	2.45	1.2	5	50	22
GZ5RL122R075	6	0.75	1.5	2.45	1.5	5	50	22
GZ5RL122R10	6	1	2	2.45	2.5	5	50	22
GZ6RL122R05	8	0.5	1	2.95	1.2	6	50	22
GZ6RL122R075	8	0.75	1.5	2.95	1.5	6	50	22
GZ6RL122R10	8	1	2	2.95	2.5	6	50	22





益詮精密股份有限公司
ECHAINTOOL PRECISION CO., LTD.



台灣精品 2008
TAIWAN EXCELLENCE



設計優良產品
GOOD DESIGN PRODUCT



第22屆小企業獎
The 22nd Small Enterprise Award



第22屆小企業獎
The 22nd Small Enterprise Award



第22屆小企業獎
The 22nd Small Enterprise Award

內外徑車刀系列

Boring Bar & Tool Holder With Coolant Series

30 Bar Mini
300 Bar Max



雙向直噴水孔系列

Two-way direct injection water hole series

外徑中心出水車刀架

Centre Coolant Fed Clamp Tool Holder



全球獨步下壓板引導式水孔

Globally stepped down platen-type water hole

可由刀架側面及刀架下方皆可接入高壓水管

High pressure water pipes can be accessed from the side of the tool holder or under the tool holder.



模具鋼抗震刀柄中心出水

Alloy Tool Steel Shank Central coolant With Oil Hole

壓板固定式出水內徑車刀

Top Clamping Coolant Boring Bar

可四倍抗震! It's Quadruple Seismic Performance



台灣精品 2008
TAIWAN EXCELLENCE

設計優良產品
GOOD DESIGN PRODUCT

第22屆小巨人獎
The 22nd Rising Star Award

第20屆小巨人獎
The 20th Rising Star Award

佳助總代理 中國一總代理
Sumitomo Agent in China

益詮精密股份有限公司
ECHAINTOOL PRECISION CO., LTD.

端面切斷刀系列

Tool Holder For Cutting Off & External Grooving Series



專利新品

Patent new product



HOGH Series

出水端面切槽刀

Coolant Face Grooving

不用拆裝刀座，可快速定位使用

Didn't need to dismounting the tool block, can faster positioning

可做內徑端面切槽

Available for internal face grooving

HOSR Series

內徑出水端面淺槽刀

Internal Shallow Grooving
With Coolant



可進行深度淺槽加工

Deep processing in a shallow slot

特殊出水設計，有效加強排屑效率

Special design of coolant, effectively enhance chip disposal improvement

提升刀片加工壽命，降低加工成本

Increasing the inserts' life to cut down the processing cost.

EGH200-ECM100 / EGH300-ECM100

EGH400-ECM100 / EGH500-ECM100



刀片刃口專業設計

達到加工表面平坦的效果

With the special design on the blade edge it shows excellent and flat processing surface
特殊的後刀面結構使切削阻力降低20%減少振動，進一步提高加工表面
精度！特殊的刃口設計可針對機床剛性要求，可適用於小功率機床。

Special design on the flank of the insert can decrease 20% vibration and can
process the fine surface smoothly. It also lives up to the rigid requirement of
small power NC machine.

HZH Alloy Tool Steel Series

外徑抗震切斷刀

Anti-Vibration External Grooving Holder

模具鋼材質刀架

High rigid alloy tool steel can enhance sustainability

提升耐用度、加強抗震性

and anti-vibration ability with excellent working performance.





CHAIN[®]

益詮精密股份有限公司

ECHAINTOOL PRECISION CO., LTD.



Our web

TEL:+886-4-22710856 FAX:+886-4-22710857

Skype : echaintool

E-mail : sales@echaintool.com

https : //www.echaintool.com

41154 台灣台中市太平區大里工業區工業18路3-1號

No.3-1, Gongye 18th Rd., Taiping Dist.,

Taichung City, 41154, Taiwan (Da-Li Industrial Park)

中国总部 Branch In China 企业QQ : 400-606-5118

National Free Call Number (In China) : 400-606-5118

TEL : +86-0512-57005208 FAX : +86-0512-57005206

业务投诉专线 : 18020216088

广东 / 天津 / 重庆 / 武汉 均有办事处

Branch offices are located at Guangdong, Tainjin, Chongqing and Wuhan.